

ECOSYS PZ7000ix

ECOSYS PZ7000ix



A3 B&W Printer

Up to 70 ppm

10.1-inch touchscreen panel

AI-powered super resolution

ECOSYS PZ7000ix

BASIC SPECIFICATIONS

Configuration: A3 Mono single function printer
Speed: Letter: 70ppm; Legal: 42ppm; Ledger: 35ppm
Warm Up Time: 17 sec. or less
First Page Out: 3.7 sec. or less
Display: 10.1" Color Touch Screen Control Panel
Memory/Hard Disk Drive: 4GB RAM / 256 GB SSD Standard
Duplex: Standard Stackless Duplex Supports SRA3 (12X18) ~ A6R (StatementR) 60 ~ 256gsm
Standard Output Tray: Statement ~ 12" x 18" / 500 sheets; up to 12" x 48" Banner (Single Sheet)
Electrical Requirements: 120V: 60Hz, 12.0A; 220V-240V: 50/60Hz, 7.2A
Typical Electricity Consumption: 120V: 0.97 kWh/week
Dimensions: 23.7" W x 26.2" D x 31.1" H
Weight: 169.8 lbs. (77 kg)
Maximum Monthly Duty Cycle: 200,000 pages per month

PAPER SUPPLY

Paper Capacity: Standard 1,150 Sheets; Maximum 7,150 Sheets
Standard Paper Sources: Dual 500 Sheet Trays, 150 Sheet MPT, Auto Selection/Switching
Standard Paper Size: Max. SRA3 (Ledger) - Min. A6R (StatementR)
Optional Paper Sources: Dual 500-Sheet Paper Trays - Ledger (**PF-7140**); Dual 1,500-Sheet Paper Trays - Letter (**PF-7150**); 3,000-Sheet Large Capacity Side Tray - Letter (**PF-7120**)
Paper Weight: Trays: 52 ~ 300gsm; MPT: 52 ~ 300gsm; Banner 136 - 163g/m2
Input Materials: Standard/Optional Tray: Plain Paper, Recycled; MPT: Plain Paper, Recycled, Thick, Thin, OHP, Index tab, Envelope, Coated

SECURITY SPECIFICATIONS

Guarded Access: Secure boot, Allowlisting, Local authentication, Windows authentication: (NTLM v2, Kerberos), Ext. authentication
Protected Data Storage: TPM, Overwrite erasure & Data Encryption (Standard)
Secure Communication: IPsec, HTTPS, SNMPv3, IPPS.POP over TLS, SMTP over TLS, Enhanced WSD over TLS; REST over TLS, VNC (RFB) over TLS, LDAP over TLS/SSL

PRINT SPECIFICATIONS

Standard Controller: ARM Cortex-A53 Dual-core 1.6 GHz
PDLs/Emulations: PRESCRIBE, PCL6 (PCL-XL/PCL-5e), KPDL3 (Compatible with PostScript3), PDF, XPS, OpenXPS, PPML
Print Resolution: 600 x 1200 dpi; 1200 x 1200 dp; 4800 dpi equivalent x 1200dp
Fonts: 93 PCL6/136 KPDL3, 4 calibri, 4 cambria, 1 bitmap
OS Compatibility: Windows, MacOS, Chrome OS
Mobile Printing: Apple AirPrint®, Mopria®, KYOCERA Mobile Print, Kyocera Mobile Print for Students
Interfaces: Standard: 10/100/1000BaseTX, Hi-Speed USB 3.0, 4 USB Host Interfaces Front 3, Rear 1; Optional: Wireless LAN/Interface (2.4GHz/5GHz multi-band) (**IB-37**); Wireless Network Interface (2.4GHz) (**IB-38**); Gigabit Ethernet Board for Dual NIC (**IB-53**); Wireless LAN NIC - 2.4GHz/5GHz - 328' Range (**IB-54**); Wireless LAN NIC - 2.4GHz - 328' Range (**IB-55**)
Network Print and Supported Protocols: TCP/IP, FTP, LPR, Port9100, NetBEUI, Apple Bonjour, IPv4, IPv6, IPsec, SSL, HTTP, LPD, IPP, RawPort, LLTD, SNT, DHCP, SMTP, POP3, SNMPv3
Drivers: KX Driver, KX (XPS) Driver, KX(V4) Driver, GX Driver, GX(XPS) Driver, PCL Mini Driver, KPDL Mini Driver, XPS to Raster Driver, Windows Inbox Driver, Novel NDPS, KX Prescribe Macro Generator, Network Fax Driver, TWAIN Driver (Network), TWAIN Driver (USB), TWAIN Driver (Box), WIA Driver (Network) WIA Driver (USB), Status Monitor, Mac Driver, KPSL Driver for Mac, Linux Driver, LPSL Driver for Linux, SANE Driver (Network), SANE Driver (USB), Chrome OS PPD Driver
Utilities: KYOCERA Net Admin, KYOCERA Device Manager, KYOCERA Net Viewer, Quick Network Setup, Maintenance Menu, Wi-Fi Setup Tool, Removal Tool, Software Upgrade Tool, Upgrade Sync, Scan to Folder Setup Tool for SMB, Kyocera Cloud Access Mobile applications include KYOCERA Mobile Print, KYOCERA Mobile Print for Students, KYOCERA MyPanel, KYOCERA Print Service Plugin

CONSUMABLES

TK-6382: Black Toner Container; Yield: 40,000 pages; Based on printing on letter paper with 6% coverage
SH-10: Staples (5,000 pieces x 3 Cartridges/Case)
SH-12: Staples (5,000 pieces x 3 Cartridges/Case)
SH-14: Staples (5,000 pieces x 5 Cartridges/Case)

ADDITIONAL OPTIONS

Cabinet Stand: ECOSYS PZ7000ix Cabinet Stand
Stabilizer Kit: ECOSYS PZ7000ix Stabilizer Feet for Cabinet Stand
JS-7100: Job Separator
JS-7110: 250-Sheet Inner Shift Tray
DF-7120: 1,000-Sheet Finisher (50-Sheet Staple)
DF-7140: 4,000-Sheet Finisher (65-Sheet Staple)
DF-7150: 4,000-Sheet Finisher (100-Sheet Staple)
AK-7110: Attachment Kit for DF-7120, DF-7140 or DF-7150
BF-730: Booklet and Tri-Folding Unit for DF-7140
BF-9100: Booklet and Tri-Folding Unit for DF-7150
PH-7A: Punch Unit for DF-7120, DF-7140 or DF-7150
MT-730 (B): 7-Bin Mailbox for DF-7140
IS-7100: Insertor Unit
ZF-7100: Z-Fold Unit
AK-7120: Attachment Kit for the ZF-7100
W2250-15-120: Innovolt Power Filter W2250-15-120
Banner Guide 10: MPT Guide Attachment - Banner Paper Feeding
NK-7130: Numeric Keypad
UG-33: Thin Print Option
UG-34: Optional Printer Emulation
Card Authentication Kit: Card Authentication Kit (B)
HD-22 (N): Large Capacity SSD (240GB) FIPS 140-3 certified

Specifications and design are subject to change without notice. For the latest on connectivity visit kyoceradocumentsolutions.us. TASKalfa, PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Mopria is a trademark of Mopria Alliance, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners.



Kyocera Document Solutions Partner

KYOCERA Document Solutions America
225 Sand Road, PO Box 40008
Fairfield, New Jersey 07004-0008, USA
Tel: 973-808-8444



kyoceradocumentsolutions.us

Kyocera Document Solutions America, Inc. does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.
©2026 KYOCERA Document Solutions America, Inc.